

Profile® II Filters



Description

Profile II filters are proven to remove 99.98% of the contaminants at their micron rating. They are ideally suited for pre-RO, resin trap and cooling water applications.

- Excellent removal efficiency
- Continuously profiled pore structure
- High contaminant holding capacity
- Low extractables (no binders or resins)
- Available in many removal ratings and configurations
- Long service life

Specifications

Materials

- Medium: Polypropylene
- Core: Polypropylene
- Gasket: Santoprene¹ rubber

Removal Ratings

- 1 µm, 3 µm, 5 µm, 7 µm, 10 µm, 15 µm, 20 µm, 40 µm and 70 µm

Configurations

- Nominal length: 10" / 254 mm, 20" / 508 mm, 30" / 762 mm and 40" / 1016 mm
- Diameter: 2½" / 64 mm
- Double open end flat gasket

Operating Conditions

- Maximum Temperature: 180°F / 82°C
- Maximum Differential Pressure:
 - 60 psid @ 85°F / 4.1 bar @ 30°C;
 - 50 psid @ 120°F / 3.4 bar @ 50°C;
 - 30 psid @ 160°F / 2 bar @ 70°C;
 - 15 psid @ 180°F / 1 bar @ 82°C

¹ Santoprene is a trademark of Monsanto Company

Removal Rating / Pressure Drop

Cartridge Grade	Removal Rating in Microns (μm) at % Efficiency ¹		Clean Pressure Drop in Water Per 10" / 254 mm Element	
	90%	99.98%	psi / gpm	mbar / 10L / min
010	< 1	1	2.6	473
030	< 1	3	1.5	273
050	2	5	0.8	146
070	3.5	7	0.5	91
100	6.5	10	0.3	55
120	7	12	0.2	36
150	8	15	0.15	27
200	10	20	0.10	18
300	14	30	0.08	15
400	20	40	0.05	9
700	32	²	< 0.05	< 9

¹ Rating of filter is based upon the modified Oklahoma State University (OSU) F-2 Filter Performance (Beta Rating) Test.

² Precision evaluation of the 99.98% removal efficiency for these coarse grades is not possible with the OSU test procedure utilized.

Part Numbers / Ordering Information

Part Number	Removal Rating (μm)	Nominal Length ³ (in / mm)	Configuration ³ Code	Gasket Material ³
RM1F050H21	5	10 / 254	Double Open End / Flat Gasket	Santoprene
RM2F050H21	5	20 / 508	Double Open End / Flat Gasket	Santoprene
RM3F050H21	5	30 / 762	Double Open End / Flat Gasket	Santoprene
RM4F050H21	5	40 / 1016	Double Open End / Flat Gasket	Santoprene
RM1F200H21	20	10 / 254	Double Open End / Flat Gasket	Santoprene
RM2F200H21	20	20 / 508	Double Open End / Flat Gasket	Santoprene
RM3F200H21	20	30 / 762	Double Open End / Flat Gasket	Santoprene
RM4F200H21	20	40 / 1016	Double Open End / Flat Gasket	Santoprene
RM1F400H21	40	10 / 254	Double Open End / Flat Gasket	Santoprene
RM2F400H21	40	20 / 508	Double Open End / Flat Gasket	Santoprene
RM3F400H21	40	30 / 762	Double Open End / Flat Gasket	Santoprene
RM4F400H21	40	40 / 1016	Double Open End / Flat Gasket	Santoprene

³ Other lengths, configurations and gasket materials are available.

Unit conversion: 1 bar = 100 kilopascals



Microelectronics

2200 Northern Boulevard
East Hills, New York 11548-1289 USA

1.800.360.7255 toll free (Only in US)
1.516.484.5400 phone
1.516.625.3610 fax

Visit us on the Web at www.pall.com/micro

Pall Corporation has offices and plants throughout the world in locations including: Argentina, Australia, Austria, Belgium, Brazil, Canada, China, France, Germany, Hong Kong, India, Indonesia, Ireland, Italy, Japan, Korea, Malaysia, Mexico, the Netherlands, New Zealand, Norway, Poland, Puerto Rico, Russia, Singapore, South Africa, Spain, Sweden, Switzerland, Taiwan, Thailand, United Kingdom, United States, and Venezuela. Distributors are located in all major industrial areas of the world.

Filtration. Separation. Solution.SM

© Copyright 2004, Pall Corporation. Pall, are trademarks of Pall Corporation. ® Indicates a Pall trademark registered in the USA. Filtration. Separation. Solution.SM is a service mark of Pall Corporation.

E1c