



Kleenpak™ Capsules with Emflon® II Membrane

Description

Kleenpak™ capsule filters containing with hydrophobic polyvinylidene fluoride (PVDF) Emflon® II membranes are especially designed for the sterile filtration of air and gas. These compact filter capsules provide high air flows, resist blocking in wet applications, and provide 100 % removal of bacteria and viruses from air and gases, even in the presence of high humidity and moisture.

Kleenpak capsules are manufactured using gamma-irradiation tolerant materials and offer the very highest standard of filtration security and user convenience. These filters can be integrated within gamma-irradiatable or gamma-sterilized complex systems such as bioreactors, filter assemblies, or transfer sets where venting is required.

Pre-sterilized Option

Kleenpak filters can be supplied sterilized by a validated gamma-irradiation process reducing time and costs. Filter capsules are then double-bagged and the outlet is covered with a protective cap for extra security.

Gamma-irradiatable Option

The capsules can also be supplied non-sterile, allowing the connection to tubing or any other type of equipment prior to gamma irradiation. This allows users to have a sterilized processing system without the need for aseptic connections and the associated risks of contamination.

Custom-made Sets

We are happy to work with end-users to provide custom-designed processing systems which will integrate one or more of our capsule ranges.

Features and Benefits

- Highly retentive Emflon II membrane
- High flow-rates associated with low Delta P enable the use of small filters — reduction of installation and operating costs
- Gamma-irradiatable or pre-sterilized for maximum convenience
- Integral molded connections
- Fully integrity testable using the forward flow test

High Quality Standards

- Validated in liquids with *Brevundimonas diminuta* (ATCC 19146) at a challenge level of

- 10⁷ organisms/cm² of filter area
- 100 % integrity tested during manufacturing
- Identified by a lot number with a unique serial number for complete traceability of manufacturing history and for user traceability systems
- Each filter supplied with a Certificate of Test
- Comprehensive validation guide available
- Manufactured under a Quality Management System certified to ISO 9000
- Meets USP Biological Reactivity Tests in vivo, in accordance with USP Class VI plastics at 121 °C

Specifications

Materials of Construction

Membrane	Hydrophobic PVDF
Support and Drainage Layers	Polypropylene
End Cap, Core and Cage	Polypropylene
Outer Shell	Polypropylene
Vent and Drain Valve O-rings	Ethylene Propylene (EPDM)

Nominal Dimensions

	KA02	KA1	KA2	KA3
Maximum Diameter (Including Valves)	51 mm (2.0 in.)	94 mm (3.7 in.)	94 mm (3.7 in.)	109 mm (4.2 in.)
Length with Hose Barb Connections (Code 2)	104 mm (4.1 in.)	NA	NA	NA
Length with Sanitary Connections	NA	11.7 cm (4.6 in.)	15.8 cm (6.2 in.)	17.4 cm (6.8 in.)
Nominal Filtration Area	200 cm ² (0.21 ft ²)	500 cm ² (0.5 ft ²)	1000 cm ² (1.0 ft ²)	1500 cm ² (1.5 ft ²)

Operating Conditions¹

KA02


Maximum Operating Pressure	4.1 barg (60 psig) at 38 °C
Maximum Differential Pressure	2.1 barg (30 psid) at 80 °C

KA1/KA2/KA3

Maximum Operating Temperature	40 °C
Maximum Operating Pressure	3.5 barg (50 psig) at 40 °C

¹ In air/nitrogen gas service or other compatible fluids, which do not soften, swell, or adversely affect the filter or its materials of construction.

Typical Air Flow Rates²



² For gases other than air or nitrogen, contact your local Pall representative.

Sterilization

Gamma-irradiation Maximum Dosage (G option only)

Up to 50 kGy

Autoclave Sterilization:

Gamma-irradiated Filters

One 30-minute cycle at 125 °C

Non Gamma-irradiated Filters

3 x 1 hour cycles at 125 °C

Warning: Kleenpak filters must not be in situ steam-sterilized by passing steam through under pressure. The figures are maximum allowable figures determined by testing under controlled laboratory conditions to the total number of hours indicated. Actual operating conditions may affect the filters long-term response to sterilization. Filters should be qualified for each process application.

Ordering Information

Ordering Information

Code	Nominal Length	Code	Connection Type	Code	Sterilization Status
02	See above dimensions table	1 ^a	38 mm (1½ in.) sanitary flange	S	Gamma-irradiated
1		2	6 – 13 mm (¼ – ½ in.) hose Barb	G	Non-irradiated
2		8 ^b	13 mm (½ in.) sanitary flange		
3					

^a For KA1, KA2 and KA3 sizes only.
^b For KA02 size only.

Contact Information

© Copyright Pall Corporation

Visit us on the Web at www.pall.com